



TC320

Business Analog Portable Radio

Unique for its compact and professional design, as well as its superb sound quality. Its strong casing prevents damage against drops of up to 5ft. This radio enables businesses to enjoy dependable communications at an extremely low cost.



Highlights

- **Wide Communication Range**
2W output power has a range of up to 6 miles.
- **Durable Casing**
Compact durable design that can withstand a 1.5 meter drop.
- **Long Battery Life**
1700mAh high capacity Li-Ion battery lasts approximately 12hrs.
- **User Friendly Design**
With its ergonomic design, this slim and compact radio can enhance user comfort, while maintaining a professional and fashionable appearance.
- **Double Injection Molding**
The combination of double injection molding and grip technology brings users a comfortable and convenient operation experience.
- **Mini-USB Interface**
Chargeable and Programmable through the Mini-USB port, plug directly into an outlet or the optional charger.

Features

- Audio Compressor
- Scrambler compatible w/ TC320 UHF2 & TC518
- VOX Earpiece
- Battery Strength Indicator
- High / Low Power Switchable
- Programmable 25 / 12.5 KHz Channel Spacing
- Monitor
- CTCSS / CDCSS and Squelch Tail Elimination
- Channel Scan
- Auto Battery Save
- Low Battery Alert
- Busy Channel Lockout (BCL)
- Time-out-timer (TOT)
- PC Programmable
- Wired Clone

Applications

Retail Hotel Restaurants Education Hospital Business Property Management



Accessories

- Included
- Li-Ion Battery
 - Power Supply
 - Antenna
 - Belt Clip
 - Neck Strap

Optional

See website for full list



Ear set with In-Line MIC EHS12-A



Rapid-rate Charger (for Li-Ion Battery) CH05L01



Programming Cable (USB Port) PC30



6-Unit Switching Power (Combine w/ CH05L01) PS4001

Specifications

General	Frequency Range	UHF1: 400 - 470MHz
	Channel Capacity	16
	Channel Spacing	25 / 12.5KHz
	PLL Channel Stepping	5 kHz, 6.25 kHz
	Operating Voltage	3.7V (rated)
	RF Power Output	2W
	Battery	1700mAh (Li-Ion)
	Battery Life (5-5-90 Duty Cycle)	Approx. 10hrs
	Frequency Stability	±0.5ppm
	Operating Temperature	-4° F ~ 131° F
	Antenna Impedance	50 Ω
	Dimensions (HxWxD)	3.94 x 1.89 x 1.06 Inches
	Weight	4.76oz
	FCC ID	See website for full list
	Canada Industry ID	See website for full list



Hytera_TC-320_DS

HYT, Hytera are registered trademarks of Hytera Communications Co., Ltd.
© 2024 Hytera Communications Co., Ltd. All Rights Reserved.
Hytera retains right to change the product design and specification.



Hytera US Inc.
8 Whatney, Suite 200, Irvine, CA 92618
(954) 846-1011
1363 Shotgun Road, Sunrise, FL 33326
(954) 846-1011
www.hytera.us
info@hytera.us